Conex | Bänninger

Delcop End Feed

KEKALBOLEH SDN BHD (199901021248/496148-K) Lot No. 7, Lorong Perindustrian Kolombong Jaya, Pusat Perindustrian Kolombong Jaya, Mile 5.5, Jalan Kolombong, 88450 Kota Kinabalu, Sabah. Tel/WhatsApp: 088-385555 / 013-8867570 Website: kekalboleh.com


A range of copper capillary soldering and brazing fittings.



Features and Benefits:

- Available in sizes 6-54mm.
- Suitable for connecting copper tubes in accordance with EN 1057.
- Designed for soldering and brazing application with the exception of union fittings with copper tail, which cannot be brazed.
- Manufactured with copper and gunmetal which are immune to dezincification.


Conex Delcop End Feed fittings (Silver brazing)			
Size (mm)	Working Pressure (bar)		
	-20° to 110°C	150°C	200°C
6	79.1	67.3	35.6
8	57.9	49.2	26.1
10	45.7	38.8	20.5
12	37.7	32.0	17.0
15	35.1	29.8	15.8
18	33.3	28.3	15.0
22	30.6	26.0	13.8
28	23.8	20.3	10.7
35	21.1	17.9	9.5
42	19.3	16.4	8.7
54	16.3	13.9	7.3



Conex | Bänninger

Delcop End Feed

Delcop Endfeed Range






























Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM. Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: salesuk@ibpgroup.co.uk | Website: www.ibpgroup.com

